



## STALLION 4x4

## **SPECIFICATIONS**

221 hp (165 kW) at 2500 rpm
800 Nm at 1400 – 1900 rpm
250 litres
Manual 6 speed
Fullly floating single speed, With
Diff lock
Twin speed
Fully floating single speed, Driven
axle, steerable

SUSPENSION			
Туре	Semi-elliptic multi leaf spring at front & rear		
STEERING			
Туре	Integral Power Steering LH		
DDAKEO			
BRAKES			
Туре	Full Air - Dual Line		
ELECTRICAL SYST	EM		
System Voltage	24 V		
Batteries	150 AH		
WHEELS & TYRES			
WHEELS & LIKES	44.00 00.00 PD 0011 Talk-		
Tyre Size	14.00 x 20-22 PR SCH, Tube Tyre		
CAB			
Sleeper Cabin, AC provision - optional			
-			


DIMENSIONS (mm)	
Wheel Base	4500
Overall Length	7425
Overall Height	3110 (over body)
Overall Width	2500
Ground Clearance atFront and Rear	350
Angle of Approach/Departure	30°/ 30°


)
)

PERFORMANCE	
Max Speed (Geared)	100 kmph
Max. Gradeability	25°
Min. Turning Circle Diameter(TCD)	18.5 m

CONFIGURATION	
Drive	LHD

## DIMENSIONS





Note: Ashok Leyland Ltd. has a policy of continual product improvement. The specifications shown here are indicative and are subject to change without prior notice.